

Model HS-5300

Motion Activated Alarm

...For a secure zone in any room.

- 90° Motion Sensor Can Be Aimed for Optimum Sensitivity - detects motions up to 60 feet away!
- Select Between Two Sounds
 - Loud 105 decibel siren
 - Chime tone
- Programmable Personal Security Code
- Selectable Entry Delay 5, 10 or 15 seconds
- Adjustable Alarm Time 30, 60 or 90 seconds
- 60 second Exit Delay
- Low Battery Indicator
- Table/Wall Mountable
- Portable
- Includes Window/Door Warning Stickers
- 90 Day Limited Warranty
- Requires One 9V Alkaline Battery (not included)





Ideal for:

- Houses
 - Entrance Ways
 - Patio Entrances
 - Garages
- Apartments
- Hotel Rooms
- Offices
- RVs and Boats
- Retail Stores

HS-5300						
	Size		Weight		Cube	UPC #
	English (inches)	metric (mm)	lbs.	kg.	Guso	5. 5 "
Giftbox	7.4 x 3.2 x 9.8	188 x 81 x 246	.54	.25		0-42741-05300-6
Master Carton (12 pcs)	20 x 7.7 x 10.3	526 x 201 x 262	7.0	3.2	.27 Ft. ³	1-00-42741-05300-3

ADDITIONAL OTHER VOLTAGES & FREQUENCIES AVAILABLE OTHER COUNTRY REGULATORY APPROVALS AVAILABLE OEM PROJECTS

UNIVERSAL SECURITY INSTRUMENTS, INC.

11407 CRONHILL DRIVE, SUITE A
OWINGS MILLS, MARYLAND 21117 USA

TELEPHONE: 410-363-3000 • FAX: 410-363-2218 • E-MAIL: sales@universalsecurity.com

Visit Us on the Web! www.SmokeAlarms.com