



**Model USI-2430**

**Heat Alarm, 120 Volt AC/DC**

- 135°F (57°C) Fixed Temperature Heat Alarm
- 9V Battery Backup in Event of AC Power Failure
- Includes 9 Volt Super Heavy Duty Battery
- Interconnectable up to 24 units (12 units must be smoke alarms). When unit goes into alarm, all interconnected units sound their alarm.
- Initiating Alarm Feature - when heat is detected, the red LED flashes on the initiating heat alarm
- Green LED indicator for AC power
- Separate large size 5<sup>5</sup>/<sub>8</sub>" (143mm) Mounting Ring Attaches to any Standard Rectangular or Octagon Junction Box and Covers Drywall Cutout
- Fast and Easy Installation
- Test Button
- 120 VAC (60 Hz) Power
- Wire Harness for Easy Connection
- Loud 85 Decibel Horn
- Five Year Limited Warranty

**USI ELECTRIC brings over four decades of manufacturing expertise to a full line of safety products.**



All USI ELECTRIC Smoke & Fire Alarms comply with the following authorities: Underwriters Laboratories (UL), Underwriters Laboratories Canada (ULC), Federal Housing Authority (FHA), Housing and Urban Development (HUD), National Fire Protection Association (NFPA), California State Fire Marshal (CSFM 7254-0899:0110)

USI-2430						
	Size		Weight		Cube	UPC #
	English (inches)	metric (mm)	lbs.	kg.		
Giftbox	5.62 x 5.62 x 2.17	143 x 143 x 55	.54	0.24	-----	0-42741-02430-3
Master Carton (24 pcs)	14.125 x 11.875 x 12.125	359 x 302 x 308	14.0	6.35	1.18 Ft. <sup>3</sup>	1-00-42741-02430-0
USI-2430-6P (6 pc Master)	6.37 x 6.37 x 13.77	162 x 162 x 350	3.24	1.47	0.04 Ft. <sup>3</sup>	1-00-42741-62430-2

**USI ELECTRIC, INC.**  
 11407 CRONHILL DRIVE, SUITE A  
 OWINGS MILLS, MARYLAND 21117 USA  
 TELEPHONE: 800-390-4321 • FAX: 410-363-2218 • E-MAIL: sales@usielectric.com  
 Visit Us on the Web! [www.SmokeAlarms.com](http://www.SmokeAlarms.com)