



Model USI-1103-6P

Smoke & Fire Alarm, AC Electrical

- Contains 10 Year LITHIUM Battery
- Battery Backup in Event of AC Power Failure
- Silencer Feature - convenient silencer button with automatic reset allows you to temporarily override alarm - ideal for cooking smoke and fireplaces - eliminates nuisance alarms
- Dual Ionization Sensor
- Ideal for Replacement of Most Existing Smoke Alarms
- Smart Interconnect up to 18 units - with 12 Smoke Alarms maximum - when smoke is detected, all interconnected Smoke Alarms sound their alarm during alarm
- Originating Alarm Feature - when smoke is detected, the red LED flashes on the initiating smoke alarm
- Green LED indicator for AC power
- Fast and Easy Installation
- Separate Large Size 5⁵/₈" (143mm) Mounting Plate Attaches to any Standard Rectangular or Octagon Junction Box and Covers Drywall Cutout - for easy installation and coverage of drywall cutouts.
- 120 VAC (60 Hz) Power
- Wire Harness for Easy Connection
- Loud 85 Decibel Horn
- Chamber and cover designs protect alarm from insects and contaminants.
- Ten Year Limited Warranty

USI ELECTRIC brings over four decades of manufacturing expertise to a full line of safety products.



All USI ELECTRIC Smoke & Fire Alarms comply with the following authorities: Underwriters Laboratories (UL), Underwriters Laboratories Canada (ULC), Federal Housing Authority (FHA), Housing and Urban Development (HUD), National Fire Protection Association (NFPA), California State Fire Marshal (CSFM)

USI-1103-6P						
	Size		Weight		Cube	UPC #
	English (inches)	metric (mm)	lbs.	kg.		
Giftbox	5.31 x 2 x 5.31	135 x 51 x 135	.52	0.24	-----	0-42741-01103-7
Master Carton (6 pcs)	13 x 12 x 12	330 x 305 x 305	3.8	1.72	.29 Ft. ³	1-00-42741-01103-1

USI ELECTRIC, INC.
 11407 CRONHILL DRIVE, SUITE A
 OWINGS MILLS, MARYLAND 21117 USA
 TELEPHONE: 800-390-4321 • FAX: 410-363-2218 • E-MAIL: sales@usielectric.com
 Visit Us on the Web! www.SmokeAlarms.com