

# Ionization Smoke & Fire Alarm

## 9 Volt Battery Operated

**Model 2975**

**Model 2975L (10 Year Lithium Battery)**



Universal® battery operated smoke & fire alarms offer effective and trouble-free protection. The National Fire Protection Association recommends installation of smoke alarms in every bedroom, in the hallway adjacent to the sleeping areas, and on every level of the home. This alarm is suitable for installation in houses, apartments, dormitory rooms, and mobile homes.

### Features

### Benefits

Quick Draw® battery drawer	<i>Safe and convenient battery replacement</i>
Single silence/test button	<i>Temporarily quiets a non-emergency alarm and tests alarm functionality</i>
Fast and easy to install	<i>No wiring required</i>
Quick activation pull tab	<i>Preserves battery life. Pre-installed battery is quickly activated without removing alarm from bracket</i>
Audible low battery indicator	<i>Warning reminder sounds for up to 30 days</i>
10-year lithium battery	<i>Provides power for the life of the alarm (model 2975L only)</i>
2 tamper resistant locking features	<i>Prevents unauthorized alarm or battery removal</i>
Battery included	<i>9 volt super heavy-duty battery model 2975. 10-year long life lithium battery model 2975L</i>

### Technical Specifications

Sensor Type:	Ionization
Primary Power:	9 volt battery
Audible Alarm:	85 dB at 10 feet
Temperature Range:	40° F to 100° F (4° C to 38° C)
Humidity Range:	5% to 95% RH
LED:	Green=AC power, Red=alarm
Size:	5.63" x 5.63" x 1.75"
Warranty:	3 year limited

### Regulatory Compliance:

Underwriters Laboratories (UL-US)  
 Underwriters Laboratories Canada (ULC)  
 California State Fire Marshal (CSFM) 7256-0899:0116  
 National Fire Protection Association (NFPA)  
 Housing and Urban Development (HUD)  
 Federal Housing Authority (FHA)  
 UTGT / UTHA



MODEL	BRAND	Box		SHELF PACK (in.)	WEIGHT	UPC CODE	QTY	MASTER CTN (in.)		WEIGHT	I2 of 5
		Clam	QTY					W x H x D	(Lbs.)		
2975	UNIV.	CL	1	6.88 x 9.00 x 2.13	0.56	0-42741-12975-6	6	7.75 x 11.38 x 14.58	5.04	1-00-42741-12975-3	
2975L	UNIV.	CL	1	6.88 x 9.00 x 2.13	0.60	0-42741-22975-3	6	7.75 x 11.38 x 14.58	5.28	1-00-42741-22975-0	

#### Corporate Office

11407 Cronhill Dr., Suite A, Owings Mills, MD 21117

Phone: 800.390.4321

Fax: 410.363.2218

Web: www.UniversalSecurity.com www.UsiElectric.com