



UNIVERSAL
SECURITY INSTRUMENTS, INC.

Smoke + Fire Alarm with 10 Year Sealed Battery – Lithium Free

Part# AMI1061SC | Hardwired + Battery Backup

- **Advanced Intelligence** Detects *Both* Fast Flaming & Slow Smoldering Fires
- **Multi Criteria** Smoke & Fire Sensor
- **AI (Artificial Intelligence Techniques)** Used to Classify Smoke & Fire Profiles
- **Microprocessor Virtually Eliminates Nuisance Alarms** Caused by Everyday Cooking Smoke, Steam, etc.
- **No Batteries to Change**—Ever!
- **Lithium-Free** 10 Year Permanent Power
- **Alkaline Batteries** are Safer and More Eco-Friendly
- **Maintenance-Free Battery Power** Provides 10 Years of Safety Protection & ZERO Low Battery Chirps!
- **Tamper-Proof Design** Prevents Battery Removal



Technical Specifications

Part #	AMI1061SC
Power Type	Hardwired 120V AC/DC 10 Year Lithium-Free Battery Backup
Sensor Type	Smoke: Multi Criteria Ionization Smoke & Fire Sensor
Audible Alarm	85dB at 10 Feet
Temperature Range	40° F to 100° F (4°C to 38° C)
Humidity Range	10% to 95% RH (non-condensing)
Size	5.63" Diameter x 1.75" Deep
Weight	0.42 Pounds
Warranty	10 Years for Both Battery & Alarm

Packing Specifications

Part #	AMI1061SC
Brand	Universal Security Instruments
Packaging (Box or Blister)	Blister Card
Shelf Pack Quantity	1
Shelf Pack Size (inches)	7.00L x 10.75W x 2.13H
Weight (pounds)	0.49
UPC Code	0-42741-31061-1
Master Pack Quantity	3
Master Pack Size (inches)	8.75L x 11.50W x 7.75H
Weight (pounds)	2.66
12 of 5 UPC	1-00-42741-31061-8

Added Features & Benefits

- **Quick Find® Alarm Origination Feature** Easily Identifies Originating Alarm to sound in in an interconnected system
- **Alarm Lock Out Feature** Prevents Installation of Deactivated Alarm
- **Meets Code & Legislation** For 10 Year Sealed Battery Requirements
- **Tamper Proof Features** Both Alarm & Battery
- **Mounting Bracket** Backwards Compatible with Most USI & Universal Alarms
- **Alarm & Power LED's** Multi-Color Visual Notifications
- **Product End of Service Life Warning** Sounds After 10 Years of Activation
- **Interconnectable** Up to 24 Compatible Devices

**For More
Information
Contact**