For more information contact:

NOW IN STOCK

HOME SAFETY & SECURITY

Universal Smoke Sensing
Smoke & Fire Alarms

SMART ALARM UNIVERSAL SECURITY INSTRUMENTS, INC.

10 Year Sealed Alarm
NEVER REPLACE BATTERIES
2-in-1 Smoke & Fire Alarm
Eliminates Low Battery Chirps

Combines the Benefits of — BOTH — **Photoelectric & Ionization** Technology in One Alarm

IDEAL FOR INSTALLATION IN EVERY ROOM

EVERY ROOM
Protects Against BOTH Types of Fires

UNIVERSAL Smoke Sensing Technology® Smoke & Fire Alarm

Battery Powered MIE3050S

POWERED BY DURACELL LITHIUM FREE

10 YEAR PERMANENT POWER

Conforms to UL Std. 217
Model MI3050S

ETL US Intertek
Single Station Smoke Alarm

7256-0899:0114

Part # **MIE3050S**
Battery Powered
Smoke & Fire Alarm

FEATURES AND BENEFITS

- **Fast & Easy to Install**—No Wiring Required
- **Take the Guesswork Out of Proper Placement**—This Alarm is Ideal for Installation in EVERY room.
- **Replace Alarms Before They Fail**—Perfect for New or Replacement Installations
- **Combines the Benefits of Both**—Photoelectric & Ionization Technology in One Alarm
- **Microprocessor Virtually Eliminates Nuisance Alarms** Caused by Everyday Cooking Smoke, Steam, etc.
- **No Batteries to Change**—Ever!
- **Lithium–Free** 10 Year Permanent Power
- **Alkaline Batteries** are Safer and More Eco-Friendly
- **Maintenance-Free Battery Power** Provides 10 Years of Safety Protection & ZERO low battery chirps!
- **Tamper-Proof Design** Prevents Battery Removal

ADDED FEATURES & BENEFITS

- **Quick Find® Alarm Origination Feature** Easily Identifies Originating Alarm
- **Alarm Lock Out Feature** Prevents Installation of Deactivated Alarm
- **Meets Code & Legislation** For 10 Year Sealed Battery Requirements
- **Tamper Proof Features** Both Alarm & Battery
- **Mounting Bracket** Backwards Compatible with Most USI & Universal Alarms
- **Alarm & Power LED's**
- **Product End of Service Life Warning** Sounds After 10 Years of Activation

TECHNICAL SPECIFICATIONS

Part #	MIE3050S
Power Type	10 Year Lithium-Free Battery Powered
Sensor Type	**Smoke:** Universal Smoke Sensing Technology®
Audible Alarm	85dB at 10 Feet
Temperature Range	40º F to 100º F (4ºC to 38º C)
Humidity Range	10% to 95% RH (non-condensing)
Alarm Size	5.63" Diameter x 1.75" Deep
Alarm Weight	0.42 Pounds
Warranty	10 Years for Both Battery & Alarm

PACKAGING SPECIFICATIONS

Part #	MIE3050S
Brand	Universal
Packaging (Box or Clam)	Blister Card/Clam
Shelf Pack Quantity	1
Shelf Pack Size (inches)	7.00**L** x 10.75**W** x 2.13**H**
Weight (pounds)	0.49
UPC Code	042741530507
Master Pack Quantity	6
Master Pack Size (inches)	7.75**L** x 11.63**W** x 15.75**H**
Weight (pounds)	4.25
I2 of 5 UPC	10042741530504